



## Glass Door & Perforated Back Door



More Details :



Maximum Static Load  
1500 kg



### Features :

1. 19" and 24" Closed rack type available.
2. Transparent Glass front door & Perforated back door provide protection & cabinet inside view.
3. Square perforation at front door and back door.
4. Numbered "U" positions.
5. Multifunctional roof design for cable entry, fan tray and aisle containment installations.
6. Top and bottom available with cable entry.
7. Easily Adjustable 19" mounting depth.
8. Dual section side panels with locking allows for easy removal / installation.
9. Easily adjustable levelling feet and casters.
10. Easy to assembled or disassembled.
11. Powder coating with chemical pre treatment, compact structure and high precision.
12. Various optional accessories.

### Specification 19" Glass Door & Perforated Back Door

Part Number	Size	Width (mm)	Height (mm)	Depth (mm)
NC20-10900-GG/GB	20U	600	1045	900
NC20-11150-GG/GB	20U	600	1045	1150
NC30-10900-GG/GB	30U	600	1490	900
NC30-11150-GG/GB	30U	600	1490	1150
NC42-10900-GG/GB	42U	600	2025	900
NC42-11150-GG/GB	42U	600	2025	1150
NC45-10900-GG/GB	45U	600	2160	900
NC45-11150-GG/GB	45U	600	2160	1150

### Specification 24" Glass Door & Perforated Back Door

Part Number	Size	Width (mm)	Height (mm)	Depth (mm)
NC42-20900-GG/GB	42U	800	2025	900
NC42-21150-GG/GB	42U	800	2025	1150
NC45-20900-GG/GB	45U	800	2160	900
NC45-21150-GG/GB	45U	800	2160	1150