



Perforated Door & Back Metal Door



Maximum Static Load
1500 kg



Specification 19" Perforated Door & Back Metal Door

Part Number	Size	Width (mm)	Height (mm)	Depth (mm)
NC20-10900-PG/PB	20U	600	1045	900
NC20-11150-PG/PB	20U	600	1045	1150
NC30-10900-PG/PB	30U	600	1490	900
NC30-11150-PG/PB	30U	600	1490	1150
NC42-10900-PG/PB	42U	600	2025	900
NC42-11150-PG/PB	42U	600	2025	1150
NC45-10900-PG/PB	45U	600	2160	900
NC45-11150-PG/PB	45U	600	2160	1150

Specification 24" Perforated Door & Back Metal Door

Part Number	Size	Width (mm)	Height (mm)	Depth (mm)
NC42-20900-PG/PB	42U	800	2025	900
NC42-21150-PG/PB	42U	800	2025	1150
NC45-20900-PG/PB	45U	800	2160	900
NC45-21150-PG/PB	45U	800	2160	1150

Features :

1. 19" and 24" Closed rack type available
2. Perforated door enable ventilation and protection
3. Hexagon perforated to ensure maximum air flow
4. Various optional accessories
5. Precise dimension and craftsmanship
6. Top and bottom with cable entry
7. High quality powder coated
8. Easy removable with dual section side panels
9. High quality adjustable screw leveling feet
10. Easy to assembled or disassembled
11. Compact structure for strong build quality and high precision
12. Compatible with the LED Lights in the front and rear section rack (Optional).