


Perforated Door and Split Door



Maximum Static Load
1500 kg



More Details :



Features :

1. 19" and 24" Closed rack type available.
2. Perforated front door & rear split door provide excellent ventilation and protection.
3. Hexagon perforation at front & rear door.
4. Numbered "U" positions.
5. Multifunctional roof design for cable entry, fan tray and aisle containment installations.
6. Top and bottom available with cable entry.
7. Easily Adjustable 19" mounting depth.
8. Dual section side panels with locking allows for easy removal / installation.
9. Easily adjustable levelling feet and casters.
10. Easy to assembled or disassembled.
11. Powder coating with chemical pre treatment, compact structure and high precision.
12. Various optional accessories.

Spesification 19" Perforated Door & Split Door				
Part Number	Size	Width (mm)	Height (mm)	Depth (mm)
NC20-10900-M/T	20U	600	1045	900
NC20-11150-M/T	20U	600	1045	1150
NC30-10900-M/T	30U	600	1490	900
NC30-11150-M/T	30U	600	1490	1150
NC42-10900-M/T	42U	600	2025	900
NC42-11150-M/T	42U	600	2025	1150
NC45-10900-M/T	45U	600	2160	900
NC45-11150-M/T	45U	600	2160	1150

Part Number	Size	Width (mm)	Height (mm)	Depth (mm)
NC42-20900-M/T	42U	800	2025	900
NC42-21150-M/T	42U	800	2025	1150
NC45-20900-M/T	45U	800	2160	900
NC45-21150-M/T	45U	800	2160	1150