



CABINET SPECIFICATIONS :

- Material Cold steel 2mm with Finishing Outdoor Powder Painting Exterior
- RAL7035
- 100mm Plinth
- Glass Front door
- Solid back metal door
- Removable aluminum Bottom gland plate, THK. 5 mm
- 2 Set 19" Mounting Angle
- Handle
- Lock Insert
- Document Holder (rear)
- Door switch (front & rear) and lamp (rear)
- 1 Unit Schneider NSYCVF300M230PF ClimaSys forced vent. IP54, 300m³/h, 230V, with outlet grille and filter G2 (Exhaust Fan)
- 1 Unit Schneider NSYCAG223LPF outlet grille plast cut out 223x223mm ext dim 268x248mm, IP54 and filter G2
- 1 Unit PDU 8 Outlet Schuko, 16A Surge Protection With Switch On/Off
- 20 Pcs Cage nut and Bolt M6 Stainless Steel
- 2 Unit Grounding bar, cu tin plated 10 holes suitable for 25 sqmm (W.25mm x L.265mm x T.3mm)
- 2 Unit Thermostat Schneider NSYCCOHI
- 4 Unit Eye bolt Stainless Steel
- 2 Unit Door Stopper
- Bolt, nut, washer, screw Stainless Steel (rack fastener)
- Swing handle with flat rod control for rod with dual catch
- Include IP Rate Self Certificate



More Details :