

## KH1508A



- One KVM console control up to 8 directly connected computers.
- By daisy chaining up to 31 additional KH1508A switches, as many as 256 computers can be controlled from the original KVM console.
- Superior Video Quality- Supports the video resolutions up to 1920 x 1200 @60Hz for up to 30 meters\*, 1600 x 1200 @60Hz for up to 40 meters, and 1280 x 1024 @75Hz for up to 50 meters.
- Three port selection methods: Manual (via front panel pushbuttons), Hotkey, and multi-language OSD (On Screen Display).

## KH1516Ai



- Superior Video Quality – supports input video resolutions up to 1920 x 1200 @ 60 Hz\* up to 30 meters, 1600 x 1200 @60Hz up to 40 meters, and 1280 x 1024 @ 75 Hz up to 50 meters.
- Panel Array Mode.
- Supports TLS 1.2 data encryption and RSA 2048-bit certificates to secure users log in from browser.

## CS1308



- One USB-PS/2 console controls 8 computers; Cascade up to 2 levels - control up to 64 computers.
- Broadcast mode - operations simultaneously performed on all selected computers, software installation and upgrading, system wide shutdown, etc.
- Computer selection via front panel push buttons, hotkeys and multilingual on-screen display (OSD) menu.
- Video DynaSync™ - Exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports.

## CE700A



- Cat 5e cable connects the Local and Remote Units - up to 150m apart.
- Dual console operation - control your system from both the local and remote USB keyboard, monitor, and mouse consoles
- High resolution video - up to 1920 x 1200@60Hz (30m ); 1600 x 1200@60Hz (100m); 1280 x 1024@60Hz (150m)
- Automatic gain control - adjusts signal strength to compensate for distance

### KA7570



### KA7166



### KA7183



### 2L-7D03UDX5



### 2L-5210P

